



# **Bullet 2E 4MP**

Model: IPC-F42FP-D

4MP H.265 Bullet Wi-Fi
Baby Monitor Camera

Bullet 2E 4MP delivers 4MP live monitoring with a choice of 2.8mm/3.6mm/6mm lens option, it supports four night vision modes for clear-as day clarity even in pitch dark. Human Detection allows you to monitor what matters without receiving annoying false alerts. With IP67 certified, the camera can be used as wall mounted camera under different weather conditions.





#### **Human Detection**

Quickly find human targets in you home



### **Smart Color Night Vision**

Support four-mode night vision for clear-as day clarity even in pitch dark





#### **IP67**

Weatherproof from dust and water



### **Built-in Microphone**

High quality microphone picks up sounds clearly while monitoring



### **Diversified Storage**

Supports NVR, Cloud Storage or Micro SD card (up to 256GB)



### **Alarm Notification**

Sends instant motion-activated alerts to your mobile phone



### Wi-Fi Connection

IEEE802.11b/g/n(2.4GHz)



### Stay close with what you care

With Cloud service, you will have access to what you care as long as Internet is available. You can record daily or motion videos on Cloud and play back anytime anywhere.





## **Specifications**

### Camera

1/2.7"4 Megapixel Progressive CMOS

4MP(2560 x 1440)

Night Vision: 30m(98ft) Distance 2.8mm/3.6mm/6mm Fixed Lens

Field of View: 2.8mm;  $106^{\circ}(H)$ ,  $56^{\circ}(V)$ ,  $125^{\circ}(D)$ 

3.6mm: 92°(H), 48°(V), 109°(D) 6mm: 55°(H), 31°(V), 62°(D)

### Video & Audio

Video Compression: H.265/H.264

Up to 25/30 fps Frame Rate

16x Digital Zoom Built-inMic

### **Notice Management**

Motion Detection Configurable Region Human Detection

### What's in the box

- 1x Camera
- 1x Quick Start Guide
- 1x Power Adapter

### Network

1 x 100Mbps Ethernet Port Wi-Fi:IEEE802.11b/g/n, Dual Antenna Imou App: iOS, Android ONVIF

### Auxiliary Interface

Micro SD Card Slot (up to 256GB) Reset Button

### General

DC 12V1A Power Supply

Power Consumption:<5.1W

Material: Plastic

Working Environment:- $30^{\circ}$ C $^{\sim}$ + $60^{\circ}$ C, Less Than 95%RH Dimensions:  $147.7 \times 74.2 \times 74.2$ mm (5.8 × 2.9 × 2.9inch)

Weight: 280g (0.62lb)

CE, FCC, IP67

- 1x Screw Package
- 1x Installation Position Map
- 1x Waterproof Connector

