



## Nexans S/FTP Installation Cable Cat.7

Nexans S/FTP Category 7 high end cables are manufactured in accordance with ISO IEC 61156 requirements. It is the best choice to support all Class E, EA and Class F applications like Ethernet, Fast Ethernet, Gigabit, Ethernet, 10 Gigabit Ethernet. The Nexans Cat 7 S/FTP cables are suitable for voice, data, CATV and sharing application installations up to 1000 MHz.

Nexans Cat.7 cables, combined with a similar class of performance connectivity, are suitable for voice and data installations according to ISO/IEC 11801, EN 50173 and TIA/EIA 568 standards.

## **Technical Specifications**

- Category 7, AWG 23 bare copper conductor
- 4 individually screened pairs (PIMF)
- Tin plated copper braiding overall screen
- LSZH Jacket, orange
- Fast-, Gigabit- & 10 Gigabit Ethernet
- Power over Ethernet, Cable sharing
- EN 50173; EN 50288-4-1; ISO/IEC 11801; ISO/IEC 61156-5
- Fire safety class: FRNC-C








## Standard 4 Pairs (4x2xAWG 23)

| Part no. | Length<br>(m) | Packaging      | Dimension<br>(mm) | Weight<br>(kg) |
|----------|---------------|----------------|-------------------|----------------|
| CQ4100S  | 100           | Ring / Coil    | 280 x 150         | 5              |
| CQ4200S  | 200           | Karton / Box   | 400 x 400 x 280   | 11             |
| CQ4500S  | 500           | Trommel / Drum | 445 x 400         | 27             |
| CQ4000S  | 1000          | Trommel / Drum | 605 x 295         | 56             |



- [1] Conductor: 23AWG solid bare copper
- [2] Insulation : Polyethylen (EN 50290-2-23) Two insulated conductors twisted to a pair
- [3] Screen: ALU/PET on each pair. Alu outside 4/2 laid up together
- [4] Tinned copper braid
- [5] Outer Jacket: LSZH orange 7.0 mm outer diameter





