

Video-intercoms / Hikvision / Monitors

DS-KH6110-WE1

HIKVISION



Features

- Hikvision
- TCP/IP and WiFi
- TFT touch screen for video door entry system of 4.3"
- PoE IEEE802.3af
- Built-in microphone and speaker
- Internal calls between devices
- Bidirectional audio
- Surface mounting
- Multiple screen extensions
- Push notifications through Hik-Connect app

Specifications

Brand	Hikvision
Model	DS-KH6110-WE1
Operating system	Linux
Screen type	4.3" color touch-screen TFT
Screen resolution	480 x 272
Operation mode	9 x Operating touch buttons (call functions, menu actions and door opening)
Inputs	Does not have
Outputs	Does not have
Audio	Two-way audio with integrated microphone and loudspeaker Noise reduction and echo cancellation
Memory	Does not have
Connection	Ethernet 10/100 BaseT / RTSP / SIP Protocol 2.0 / WiFi 802.11 b/g/n (only for connection to app via P2P)
Remote access	Software iVMS-4200 Hik-Connect mobile app
Power	DC 12 V / 1 A max. / IEEE802.3af PoE
Temp. operation	-10° C ~ +50° C
Dimensions	120 (H) x 120 (W) x 21 (D) mm
Weight	198 g
Slave monitors	It is not possible to use the Android DS-KH9310 and DS-KH9510 monitors as slaves