

Video-intercoms / Hikvision / Kits

DS-KIS606-P

HIKVISION



Features

- Hikvision
- Video intercom kit
- Tecnología IP & WiFi
- Kit consisting of: DS-KV6113-WPE1(C) outdoor surface video door entry panel with 2 Mpx HD camera and DS-KH6110-WE1 indoor WiFi monitor with 4.3" TFT LCD screen
- Allows to add up to 16 additional monitors as extensions
- MF Card Reader
- Monitoring through iVMS-4200 software or Hik-Connect mobile app

Specifications

DS-KABV6113-RS/Surface

Brand	Hikvision
Model	DS-KABV6113-RS
Compatibility	Plates DS-KV6103-PE1 and DS-KV6113-WPE1
Material	Methacrylate
Dimensions	150 (H) x 80 (W) x 49 (D) mm
Mounting	Surface

DS-KV6113-WPE1(C)

Brand	Hikvision
Model	DS-KV6113-WPE1(C)
Operating system	Linux
Image sensor	1/3" 2 Mpx CMOS wide-angle IR
Image Functions	BLC / WDR / DNR
Viewing angle	H: 131°, V: 78°
Audio	Bidirectional audio with microphone and speaker
Access control	Door opening with MF card 13.56 MHz Up to 2.000 users and 10.000 cards
Keypad	Mechanical call button
Outputs	1 x relay for lock, 1 x RS485
Inputs	4 x auxiliary inputs (output button, feedback, door sensor), 1 x tamper
Remote access	Web browser Software iVMS-4200 Hik-Connect mobile application
Network interface	Ethernet 10/100 BaseT / SIP Protocol 2.0 / WiFi (only for app connection via P2P)
Power	DC 12 V / 1000 mA máx. / IEEE802.3af PoE
Degree of protection	Suitable for exterior IP65

Material	Plastic
Temp. operation	-40° C ~ +55° C
Dimensions	138 (H) x 65 (W) x 27 (D) mm
Weight	265 g

DS-KH6110-WE1

Brand	Hikvision
Model	DS-KH6110-WE1
Operating system	Linux
Screen type	4.3" color touch-screen TFT
Screen resolution	480 x 272
Operation mode	9 x Operating touch buttons (call functions, menu actions and door opening)
Inputs	Does not have
Outputs	Does not have
Audio	Two-way audio with integrated microphone and loudspeaker Noise reduction and echo cancellation
Memory	Does not have
Connection	Ethernet 10/100 BaseT / RTSP / SIP Protocol 2.0 / WiFi 802.11 b/g/n (only for connection to app via P2P)
Remote access	Software iVMS-4200 Hik-Connect mobile app
Power	DC 12 V / 1 A max. / IEEE802.3af PoE
Temp. operation	-10° C ~ +50° C
Dimensions	120 (H) x 120 (W) x 21 (D) mm
Weight	198 g
Slave monitors	It is not possible to use the Android DS-KH9310 and DS-KH9510 monitors as slaves